

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 017 232 A1**

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
05.07.2000 Bulletin 2000/27

(51) Int Cl.7: **H04N 5/232**

(21) Application number: **99309992.8**

(22) Date of filing: **10.12.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **31.12.1998 US 114728**
20.09.1999 US 399432

(71) Applicant: **LUCENT TECHNOLOGIES INC.**
Murray Hill, New Jersey 07974-0636 (US)

(72) Inventor: **Bahram, Ghaffarzadeh Kermani**
Whitehall, PA 18052 (US)

(74) Representative:
Johnston, Kenneth Graham et al
5 Mornington Road
Woodford Green Essex, IG8 OTU (GB)

(54) **Camera with configurable focus area**

(57) An imaging device having a configurable focus area comprising: (a) an imaging system for generating a video signal of an image within a field of view, wherein the imaging system is adapted to adjust the focal point of the image according to an adjustment signal; and (b) a focusing system comprising: (i) a configuration device for facilitating configuration of a focus area within the

field of view; and (ii) autofocusing circuitry coupled to the imaging system and the configuration device, the autofocusing circuitry being configured for correlating a configured focus area to a portion of the video signal, analyzing the portion for resolution, and effecting an adjustment signal to the imaging system to adjust the focal point of the image to improve the resolution of the configured focus area.

EP 1 017 232 A1

Description

Cross Reference To Related Application

[0001] This application claims the benefit of U.S. Provisional Application No. 60/114,728 filed December 31, 1998.

Field Of Invention

[0002] This invention relates generally to auto-focus control for optics. More specifically, the present invention relates to an auto-focus control device having a configurable focus area.

Background Of The Invention

[0003] Automatic-focusing cameras are well known in the art. In a conventional camera, a viewfinder displays a field of view and a portion of that field is a focus area. The camera comprises circuitry adapted to maximize the resolution of the image within the focus area. Although widely used and usually effective, conventional auto-focusing does have its shortcomings.

[0004] One particular drawback is the tendency for the focus area to be fixed within the field of view. Typically, the focus area is located toward the center of the field of view and cannot be moved. Although such a configuration is suitable in most situations where the object of the photograph is placed in the center of the field of view, occasionally the preferred composition of the photograph places the object elsewhere in the field of view. In such a case, the object tends to be blurred because the automatic focusing is performed only in the above-mentioned focus area regardless of the position of the intended object.

[0005] To solve this problem, cameras have been developed with "focus lock" to facilitate focusing on objects other than those located in the center of the field of view. More specifically, focus lock enables a photographer to focus on an off-center object by first placing the focus area over the object (that is, centering the object), allowing the lens to focus, locking the focus, and then, with the focus locked, changing the composition of a picture (for example, positioning the object off to a side) before taking the photograph. Unfortunately, "photo-opportunities" can be missed with these cameras since the focus must be locked before composing the shot.

[0006] Other cameras have been developed with sophisticated logic and control for measuring the distance to a plurality of objects within the field of view, determining the nearest object of the plurality, and focusing on that object. The object to be brought into focus, however, is not always the nearest. Thus, the resulting photograph may be focused on the wrong object rendering the intended object blurry.

[0007] Recently, cameras have been developed having a multiplicity of focus areas which can be selected

by the user. Although affording the user with greater flexibility in composing his or her photograph, these cameras are nevertheless limited to predetermined focus areas having fixed positions and sizes.

[0008] Therefore, the applicant has identified the need for a camera having a configurable focus area that is not constrained by preset conditions. The present invention fulfills this need among others.

10 Summary Of Invention

[0009] The present invention overcomes the aforementioned problems with convention auto-focus cameras by providing for a configurable focus area. A configurable focus area enables the user to position the desired focus area anywhere within the field of view. This way, the user is not limited to predefined focus areas that may not target the object upon which the user desires to focus. Additionally, the configurable focus area of the present invention may be adapted to allow the user to adjust the size and/or shape of the area.

[0010] One aspect of the present invention is an imaging device having a focus area configuration device and supporting circuitry for configuring a focus area within the field of view. In a preferred embodiment, the device comprises: (a) an imaging system for generating a video signal of an image within a field of view, wherein the imaging system is adapted to adjust the focal point of the image according to an adjustment signal; and (b) a focusing system comprising: (i) a configuration device for positioning a focus area within the field of view; and (ii) autofocus circuitry coupled to the imaging system and the configuration device, the autofocus circuitry being configured for correlating a configured focus area to a portion of the video signal, analyzing the portion for resolution, and effecting an adjustment signal to adjust the focal point of the image to improve the resolution of the configured focus area. Preferably, the autofocus circuitry comprises a digital processor.

[0011] Another aspect of the present invention is the provision of the above-mentioned focusing system for use in an imaging device.

[0012] Yet another aspect of the present invention is the provision of the above-mentioned data processor for use in a camera's focusing system.

[0013] Still another aspect of the present invention is the provision of a method of using the above-mentioned imaging device. In a preferred embodiment, the method comprises the steps of: (a) moving the imaging device relative to an object to obtain a desired field of view; (b) manipulating the above-mentioned configuration device to position the focus area over the object within the field of view; (c) using the focusing system to improve the resolution of the focus area; and (d) activating a video signal processing system to transfer the video signal to a storage medium.

Brief Description Of The Drawings

[0014] The invention may best be understood by reference to the following description taken in conjunction with the accompanying drawings, wherein like reference numerals identify like elements, and wherein:

FIG. 1 shows a schematic diagram of the present invention;

FIG. 2 shows a preferred imaging device embodiment of the invention;

FIGs. 3a-c show the correspondence between the field of view and the configuration device of the preferred embodiment of FIG. 2;

FIG. 4 shows a block diagram of the circuitry of a preferred embodiment of the present invention; and

FIG. 5 shows a preferred process performed in the imaging processing unit of FIG. 4.

Detailed Description Of the Preferred Embodiment

[0015] Fig. 1 shows a schematic diagram of a preferred embodiment of the present invention. Depicted is a device 10 which may be a still camera, video camera, microscope or other convention image sensing apparatus requiring the adjustment of optics to bring an image of an object into focus. For illustrative purposes, the device 10 has been divided into systems and discrete components. It should be noted, however, that the circuitry described herein can be integrated or further divided into discrete components without departing from the scope of the invention.

[0016] In device 10, a video signal 1 of the object is generated in an imaging system 9. The Imaging system 9 comprises adjustable optics system 11 for forming an image and an image sensor 12, such as a charge couple device (CCD), having an image sensing plane 12a for providing a video signal of an image formed thereon by the optics system. The adjustable optics system 11 has the necessary circuitry and actuating means to adjust the focal point of the image on the image sensing plane according to the input of an adjustment signal 2.

[0017] A data processor 20 such as a microprocessor or a digital signal processor receives the video signal 1 from the imaging system 9. The data processor 20 is coupled to a viewfinder 14 and provides it with a display signal 3 such that viewfinder 14 displays a field of view corresponding approximately to the image formed on the image sensing plane 12a. It is also preferable for the viewfinder 14 to display a "focus area" within the field of view. As used herein, the term "focus area" refers to that area of the field of view which is subjected to autofocus-ing. The focus area may be displayed in the field of view, for example, as a shaded portion or as an outlined

shape. Although the focus area may be any shape, rectangular, circular, oval, or square areas are preferred.

[0018] The data processor 20 is coupled to a focusing system 17. Although depicted as a discrete system for illustrative purposes, the focus system 17 may be incorporated into the data processor 20, split between the data processor 20 and other circuitry, or divided into a plurality of circuits and processors depending upon the needs and preferences of the application. As shown, the focusing system 17 comprises a configuration device 19 and autofocus circuitry 18.

[0019] The configuration device 17 enables the user to configure the focus area. This configuration includes positioning the focus area anywhere within the field of view and, optionally, adjusting its size and/or shape. The configuration device may comprise one or more functional components which may be integrated or discrete. Additionally, switching may be used such that a single component has multiple functions. The functional components should be selected according to their intended purpose. For example, positioning the focus area can be performed using devices such as pointers, ball-rollers, touch pads, joysticks, and disengaged mouse-type devices. A ball-type pointer is preferred for positioning from the perspective of control and compactness. If the configuration device also configures the area and/or shape of the focus area, then additional functionality may be required. For example, a dial can be used to adjust the size or the shape of the focus area. The same dial may be used to adjust both size and shape if switching is provided between the two functions. The structure of a preferred configuration device is described in greater detail below with respect to Figs. 2 and 3.

[0020] The configuration device outputs a configuration signal 4 containing configuration information such as positional data and perhaps area data and/or shape data of the focus area. Positional data may relate to, for example, Cartesian or polar coordinates corresponding to the position of focus area's center within the field of view. Area data may relate to the number of cells or units contained within the focus area or a simple area measurement. Shape data may relate to the aspect ratio of the focus area.

[0021] The autofocus circuitry 18 receives the configuration signal 4 from the configuration device 17 and a video signal from the optical system 9. The autofocus circuitry 18 has several functions. First, it "gates" the video signal which involves using the configuration information transmitted by configuration signal 4 to pass only the portion of the video signal emanating from the area of the image sensing plane corresponding to the focus area. Once the video signal corresponding to the focus area is identified and extracted, conventional autofocus-ing techniques may be used to effect an adjustment signal 2 to the adjustable optics system 11 thereby adjusting the focal point of the image to improve the resolution of the focus area. Suitable autofocus circuits are described, for example, in U.S. Patent No. 5,061,954 is-

sued to Toyama et al. and U.S. Patent No. 5,187,585 issued to Kaneda et al. which are hereby incorporated by reference. Preferred autofocus techniques and circuitry are described below in greater detail with respect to Fig. 4.

[0022] As shown in Fig. 1, the data processor 20 also is coupled to a signal processing system 15 for performing such functions as storing the video signal on a tangible medium such as a disk or film, or converting the video signal to a standard format for television or video. Such signal processing functions are well known in the art. To activate the processing functions, a release switch 16 may be manipulated or the functions may be performed continuously. Since the device 10 is preferably a still camera, a release switch 16 is preferred to allow the user to compose the image before processing the video signal.

[0023] Referring to Fig. 2, a perspective view of a camera 20 of the present invention is shown with an enlarged section corresponding to the configuration device 22. The camera 20 comprises a housing 21, a configurable lens assembly 27, a viewfinder 26, and the configuration device 22. The configuration device in this embodiment is a button-type pointer which is well known and widely used in laptop computers. As mentioned above, the button-type pointer is preferred from the stand point of controllability and compactness. The ball-type point comprises a stub section 23 which is connected to a base 25 via a ball and socket connection 28. The ball and socket connection allows the distal end 29 of the stub section 23 to be moved about the base 25. The position of the focus area in the field of view corresponds to the position of the distal end of the stub section relative to the base 25. This relationship is described below in greater detail with respect to Fig. 3.

[0024] In the embodiment depicted in Fig. 2, the stub section 23 is axially movable to a multiplicity of depressed positions to provide additional functionality. Preferably, the stub section has two depressed positions—a first depressed position which activates the focus system and a second depressed position which activates the video processing system. In the preferred embodiment, the configuration device also comprises means of changing the size of the focus area. Accordingly, as shown in Fig. 2, the ball-type pointer 22 preferably comprises a sleeve 24 coaxially and rotatably mounted around stub 23. Rotating sleeve 24 effects a change in the size of the focus area. It also may be preferable for the device to have means for adjusting the shape of the area. To this end, the same rotating sleeve 24 may be used for both functions, providing there is a selection switch 22a for switching between the two.

[0025] According to the configuration of the configuration device in Fig. 2, a user can conveniently compose his shot without excessive camera manipulation. Specifically, while viewing the field of view, a user can use his finger to move the stub section 23 such that the focus area is positioned over the desired object, and then, with

the same finger, depress the stub section 23 to a first-depressed position to activate the autofocus feature and focus the object within the focus area. Finally, once the user is satisfied with the shot, he can depress the stub section 23 further to a second-depressed position with the same finger to activate video processing.

[0026] Referring to Figs. 3a-c, the correspondence between the movement of the configuration device and the position of the focus area in the viewfinder is illustrated. The composition in the viewfinder 31 is the same in all three figures—a person 32 in the foreground to the left, a flag pole and flag 33 in the center background, and a cannon 34 in the right middle ground. The focus selection, however, varies in all three. In Fig 3a, the head of the person is the intended object of the shot and accordingly the focus area 36 is positioned over it by manipulating configuration device 35 such that the distal end of the stub is at approximately the 8 o'clock position. In Fig 3b, the flag atop the flag pole is the intended object of the shot and accordingly the focus area 37 is positioned over it by manipulating configuration device 35 such that the distal end of the stub is at approximately the 12 o'clock position. It is worth noting that the focus area 37 is larger than that of Fig. 3a. Increasing the focus area is accomplished by rotating the sleeve 36 of the configuration device (depicted in Fig. 3b by a change in position of hash mark 39). In Fig. 3c, the intended object is the cannon to the right, and accordingly the focus area 38 is positioned over it by manipulating the configuration device such that the distal end of the stub is pointed at about the 4 o'clock position. In this shot, the focus area 38 is expanded to include the entire cannon by rotating the sleeve 36. Therefore, the present invention accommodates selective imaging of the same composition in the viewfinder.

[0027] Referring to Fig. 4, a block diagram of a preferred embodiment of the device is depicted. The optical, focusing, and processing systems described in Fig. 1 are indicated in this figure as parted lines 65, 64, and 51, although, as mentioned above, the particular grouping of circuitry and processors can vary, and integration between the various systems and components is anticipated. The adjustable optics of the optical system comprises a focusing lens group 41 (herein "focusing lens") arranged for use as a focus adjustment. The focusing lens 41 is movable by means of a motor 42 to focus on an infinite distance position through the nearest focusing distance position. The adjustable optics also comprises a focus encoder 45 arranged to detect the moved position of the focusing lens 41. The adjustable optics includes a zooming lens which in turn comprises a variator lens 43 and a compensator lens 44. Zooming is performed by moving the variator and compensator lens relative to each other via a cam locus indicated by a broken line. A zoom encoder 46 is arranged to detect a focal length obtained by zooming. An iris unit 47 is arranged to adjust the quantity of light incident on an image sensor 50. An aperture encoder 48 is arranged to detect the

aperture position of the iris unit 47. Light passes through a master lens 49 before reaching the image sensor 50. The image sensor 50 is preferably a CCD or the like and is arranged to produce a video signal of an object image formed on its image sensing plane.

[0028] The video signal from image sensor 50 is supplied to focusing system 64. The focusing system 64 first performs a gating action on the video signal such that only video data corresponding to the focus area passes. To this end, the configuration device 63 outputs configuration information to a gate controller 54. As mentioned above, configuration information includes the positional data and optionally size and/or shape data of the focus area. Given this information, the gate controller 54 can determine the area of the image sensing plane corresponding to the focus area. In the case of a CCD array, this area can be expressed in terms of particular rows and columns of the array. It is anticipated that a similar convention may be used with other types of imaging devices. This row/column data is transmitted via a gate control signal to gate circuitry 52. The gate circuitry 52 then passes only those video data emanating from cells located in the selected rows and columns of the CCD array in a gated video signal. To facilitate digital processing of the video data, the gated video signal is converted to a digital video signal in the A/D converter 53.

[0029] Once converted, the digital video signal is suitable for processing in a data processor 58. In the data processor, the digital video signal is transmitted to a mapping unit 55 which maps video data to a fixed memory matrix 56. If the focus area is fixed, the fixed memory matrix can be appropriately sized to accommodate the extracted video data. On the other hand, if the size of the focus area is configurable, then the mapping function also may involve data culling or data interpolation if the video data is more or less than the memory matrix. In other words, if the focus area involves more video data than the matrix can accommodate, then a certain amount of video data needs to be filtered out or culled. Conversely, if the amount of video data is less than the memory matrix is configured for, then data interpolation may be required to fill the voids. Because data interpolation tends to consume a significant amount of computational resources, it is preferred that the minimum size of the focus area be limited to no less than the data required to populate the memory matrix. If the focus area is configurable, then the mapping unit should be provided with area data of the focus area so that it can determine the amount of video data to cull or interpolate.

[0030] After the video data is mapped, an image processing unit 57 processes the data to effect improved resolution or autofocus. As mentioned above, the techniques for autofocus are known in the art. A preferred process is depicted in the flow diagram of Fig. 5. As shown, in Block 501, the image processing unit 501 captures a first frame. Block 502 effects a change in the focal point of the optics by signaling the motor 42 (Fig. 4) to move in a particular direction via the system

control circuitry 62 (Fig. 4). In Block 503, a second frame is captured. Block 504 computes the difference between the first and second frames. In Block 505 a decision is made whether the focus area has achieved a desired level of resolution. If so, the process ends. If not, however, the process proceeds to Block 506 where a decision is made as to which direction to move the motor. Block 507 effects the motor's movement in a direction according to Block 506 and the process returns to Block 501.

[0031] Although a variety of data processors are suitable for performing the above-mentioned functions, the 1675 DSP microprocessor chip available through Lucent Technologies, Inc. (Murray Hill, NJ) is preferred. It also should be understood that although the preferred embodiment employs a digital microprocessor, the above-mentioned functions may be performed using discrete or integrated analog circuitry.

[0032] Referring back to Fig. 4, system control circuitry 62 is arranged to receive the encoder information of varied kinds from the focus encoder 45, the zoom encoder 48, and output from the image processing unit 57 according to the degree of focusing and to perform a computing operation on these information inputs and to produce and supply an adjustment signal to the motor driving circuit 61 for controlling the focusing lens driving motor 42. The system control circuitry 62 is preferably a microprocessor.

[0033] Once the desired resolution is achieved, the video signal output from the image sensor 50 is processed by a camera signal processing circuit 51 as described above with respect to Fig. 1.

Claims

1. An imaging device comprising:

an image sensor having an image sensing plane for providing a video signal of an image formed thereon;
 an adjustable optics system adapted to adjust the focal point of an image on said image sensing plane according to an adjustment signal;
 a viewfinder for displaying a field of view corresponding approximately to an image formed on said image sensing plane and for displaying a focus area within said field of view; and
 a focusing system comprising:
 a configuration device adapted to facilitate configuration of a focus area within said field of view, wherein configuration comprises positioning the focus area within said field of view; circuitry operatively coupled to said adjustable optics system, said image sensor, said viewfinder and said configuration device, said circuitry being configured for correlating a configured focus area to a portion of said image sens-

ing plane, analyzing the resolution of the video signal corresponding to said portion, and effecting said adjustment signal to adjust the focal point of the image to improve resolution within said configured focus area.

5

2. A focusing system for use in an imaging device having an imaging system for generating a video signal of an image within a field of view, wherein said imaging system is adapted to adjust the focal point of an image according to an adjustment signal; said focusing system comprising:

10

a configuration device for facilitating configuration of a focus area within said field of view, wherein configuration comprises positioning the focus area within said field of view; circuitry operatively coupled to said imaging system and said configuration device, said circuitry being configured for correlating a configured focus area to a portion of video signal, analyzing said portion for resolution, and effecting an adjustment signal to adjust the focal point of said image to improve resolution of said configured focus area.

15

20

25

3. The device of claim 1, or the system of claim 2, wherein said configuration device comprises a pointer adapted for manipulation by a user to position the focus area to the desired location within said field of view.
4. The device or system of claim 3, wherein said pointer is adapted for depression to a first position to activate said focus system and to a second position to activate processing of said video signal.
5. The device of claim 1, or the system of claim 2, wherein configuration of said focus area comprises sizing the focus area.
6. The device or system of claim 5, wherein said configuration device comprises a pointer adapted for manipulation by a user to position said focus area within said field of view, and an outer sleeve rotatably and coaxially mounted about said pointer, wherein rotation of said sleeve effects a change in size of said focus area.
7. The device of claim 1, or the system of claim 2, wherein configuration of said focus area comprises sizing and shaping said focus area.
8. The device or system of claim 7, wherein said configuration device comprises a pointer adapted for manipulation by a user to position said focus area within said field of view, an outer sleeve rotatably and coaxially mounted about said pointer, and a se-

30

35

40

45

50

55

lector switch having at least a first position and a second position, said selector switch being adapted such that in said first position, rotating said sleeve effects a change in focus area size, and in said second position, rotating said sleeve effects a change in focus area shape.

9. The device of claim 1, or the system of claim 2, wherein said circuitry comprises a data processor, or a digital processor, or wherein said device is a still camera.

10. The system of claim 9, wherein said digital processor comprises a gate controller for effecting an extraction of said portion of said video signal from said video signal, a fixed memory matrix, a mapping unit for mapping at least a portion of said portion to said memory matrix, and an image processing unit for analyzing the mapped portion for resolution and effecting said adjustment signal.

11. A data processor for use in an imaging device having an imaging system for generating a video signal of an image within a field of view, wherein said imaging system is adapted to adjust the focal point of said image according to an adjustment signal; and a configuration device for facilitating configuration of a focus area within said field of view; said data processor comprising:

circuitry being configured for receiving a signal from said configuration device relating to a configuration of the focus area, correlating the configured focus area to a portion of a video signal, effecting extraction of said portion from said video signal, analyzing said portion for resolution, and effecting an adjustment signal to adjust the focal point of said image to improve resolution of said configured focus area.

12. The data processor of claim 1, wherein said circuitry comprises a gate controller for effecting extraction of said portion from said video signal, a fixed memory matrix, a mapping unit for mapping at least a portion of said portion to said memory matrix, and an image processing unit for analyzing the mapped portion for resolution and effecting said adjustment signal.

13. A method of focusing using an imaging device having an imaging system and a focusing system, said imaging system generating a video signal of an image within a field of view, wherein said imaging system is adapted to adjust the focal point of said image according to an adjustment signal, said focusing system comprising a configuration device for facilitating configuration of a focus area within said field of view; and circuitry coupled to said imaging system and said configuration device, said circuitry be-

ing configured for correlating a configured focus area to a portion of video signal, analyzing said portion for resolution, and effecting an adjustment signal to adjust the focal point of said image to improve resolution of said configured focus area; said method comprising

5

moving said imaging device relative to an object to obtain a desired field of view;

10

manipulating said configuration device to position the focus area within said field of view;

using said focusing system to improve resolution of said focus area; and activating a video signal processing system to convert said video signal to storage.

15

14. The method of claim 12, further comprising:

manipulating said configuration device to adjust either the size of said focus area, and/or the shape of said focus area.

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4





FIG. 5





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 30 9992

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X A	DE 42 17 795 A (THOMSON BRANDT GMBH) 2 December 1993 (1993-12-02) * column 1, line 18 - line 32 * * column 2, line 16 - line 55 * ---	1-3,9, 11,13 4-8,10, 14	H04N5/232
X A	EP 0 399 232 A (CASIO COMPUTER CO LTD) 28 November 1990 (1990-11-28) * column 1, line 5 - line 49 * * column 7, line 35 - column 8, line 43 * * column 9, line 41 - column 10, line 4 * * column 10, line 51 - column 11, line 27 * ---	1-3,9,13 4-8,10, 12,14	
X A	US 5 349 415 A (NISHIDA YOSHIHIRO) 20 September 1994 (1994-09-20) * column 4, line 63 - column 5, line 46 * * column 7, line 38 - column 9, line 21 * -----	1-3,5,9, 11,13,14 6-8,10, 12	TECHNICAL FIELDS SEARCHED (Int.Cl.7) H04N
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 11 April 2000	Examiner Wentzel, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03 82 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 9992

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-04-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 4217795 A	02-12-1993	NONE	
EP 0399232 A	28-11-1990	JP 2288680 A	28-11-1990
		JP 2294168 A	05-12-1990
		DE 69015861 D	23-02-1995
		DE 69015861 T	07-09-1995
		DE 69017509 D	13-04-1995
		DE 69017509 T	14-12-1995
		EP 0393710 A	24-10-1990
		US 5051833 A	24-09-1991
		US 5040072 A	13-08-1991
US 5349415 A	20-09-1994	JP 2596631 B	02-04-1997
		JP 4002281 A	07-01-1992
		JP 2553757 B	13-11-1996
		JP 4170163 A	17-06-1992
		DE 69120341 D	25-07-1996
		DE 69120341 T	07-11-1996
		EP 0454354 A	30-10-1991
		KR 9503569 B	14-04-1995
		US 5210566 A	11-05-1993

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82